

Room 501,2-3 Unit No.8,Zhengzhou Road,Qingdao,China. TEL: <u>86 18661665800</u> Email: <u>Dana@ylsch-rbb.com</u> Website: <u>www.ylsch-rbb.com</u>

MATERIAL SAFETY DATA SHEET

: According to EC-directive 2001/58/EC

Rubber Accelerator DOTG HS Code: 29252900.90

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product label name Diotolylguanidine

Qingdao YLSCH Industry&Trade Co.,Ltd

Supplier Room 501,2-3 Unit. No.8,Zhengzhou Road,

Qingdao, China.

TEL: +86 18661665800

Emergency telephone TEL: +86 18661665800

Intended use Rubber Vulcanization Accelerator

2. COMPOSITION/INFORMATION ON INGREDIENTS

二邻甲苯胍 Chemical name

Diotolylguanidine

CAS NO. 97-39-2

Chemical description White powder

TSCA NO. none

EINECS NO. none

Other information C₁₅H₁₇N₃

3. HAZARDS IDENTIFICATION

Very hazardous in case of ingestion. Hazardous in case of skin contact (Irritant), of eye contact (irritant), of inhalation .very slightly hazardous in case of skin contact (permeator).severe over-exposure can result in death.

4. FIRST AID MEASURES

Dust may be irritating to the respiratory tract and cause symptoms of

Symptoms and effects bronchitis.

Repeated contact may cause skin sensitization.

First aid

General In all cases of doubt, or when symptoms persist, seek medical attention.

Inhalation Move to fresh air. If symptoms persist, seek medical advice.

Remove all contaminated clothing immediately. Wash off with plenty of



Room 501,2-3 Unit No.8, Zhengzhou Road, Qingdao, China. TEL: 86 18661665800 Email: Dana@ylsch-rbb.com Website: www.ylsch-rbb.com

Skin soap and water.

Seek medical advice if irritation develops. Launder clothes before reuse.

Eye Rinse thoroughly with plenty of water. Eyelids should be held away from

the eyeball to

Ensure thorough rinsing. Seek medical advice if irritation develops.

Ingestion Rinse mouth, give water to drink.

Advice to physician No specific recommendations

5. FIRE-FIGHTING MEASURES

Extinguishing media Waterspray, water mist, foam, dry chemical powder, CO2

Unsuitable extinguishing media Waterjet.

Special exposure hazards Explosive in presence of oxidizing materials.

Protective equipment Wear self contained breathing apparatus.

Do not allow run-off from fire fighting to enter drains or water courses. Other information

6. ACCIDENTAL RELEASE MEASURES

For personal protection see Section 8. Avoid dust

Personal precautions generation.

Avoid discharge into the environment. **Environmental precautions**

Collect as much as possible in a clean container for

Methods for cleaning up (preferable) reuse or disposal.

7. HANDLING AND STORAGE

Keep away form heat. Evaporate the residue under a fume hood.

Don't breathe dust. Avoid contact with skin and eyes.

Keep away from incompatibles such as oxidizing agents.

Storage requirements Store in a dry and cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Avoid dust generation. Ensure good ventilation and local **Engineering controls**

exhaustion of the working area.

Exposure limits

Handling

Name: Diotolylguanidine

Personal protection

Avoid breathing dust. In case of insufficient ventilation, wear Respiratory

suitable respiratory equipment.



Room 501,2-3 Unit No.8,Zhengzhou Road,Qingdao,China. TEL: <u>86 18661665800</u> Email: <u>Dana@ylsch-rbb.com</u> Website: <u>www.ylsch-rbb.com</u>

HandWear suitable gloves.EyeWear safety goggles.

Skin and body Wear suitable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	white powder	Colour	white
Odour		Boiling point	
Melting point≽	170.0℃	Flash point	
Flammability		Explosion limits	
Explosive properties		Auto ignition temperature	
Oxidizing properties		Vapour pressure	
Density	1.01-1.05g/cm3	Bulk density	
Solubility in water	Insoluble in water	Solubility in other solvents	Soluble in Chloroform, acetone,ethanol.
pH value		Partition coefficient	
Residues (150um)% Max	0.1(Max)	Relative vapour density	
Viscosity		Assay content % ≥	96
Strength of grain(N)			

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions

Stability (see section 7).

Conditions to avoid Avoid heat, flames sparks and other sources of ignition.

Materials to avoid Oxidizing agent.

Thermal decomposition products: carbon monoxide (CO),

Carbon dioxide, oxides of nitrogen. o-Toluidine.

11. TOXICOLOGICAL INFORMATION

Name Diotolylguanidine

Acute toxicity

Oral LG50 rat:>134 mg/kg.

Dermal LD50 rabbit:>2000 mg/kg.

Irritation

Skin

Slightly irritating to skin but not sufficient for classification.



Room 501,2-3 Unit No.8,Zhengzhou Road,Qingdao,China. TEL: <u>86 18661665800</u> Email: <u>Dana@ylsch-rbb.com</u> Website: <u>www.ylsch-rbb.com</u>

Eye

Slightly irritating to eyes but not sufficient for classification.

12. ECOLOGICAL INFORMATION

NameDiotolylguanidineEcotoxicityNot available.BOD5 and CODNot available.

Degradation BioticNot readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Product Avoid discharge into the environment

Small quantities: According to local regulations.

Large quantities: Consult YLSCH Chemical for special advice.

Contaminated packaging According to local regulations.

Waste code number: Please refer to your specific industry

Other information in the European Waste Catalogue.

14. TRANSPORT INFORMATION

Land transport (ADR/ RID)

ADR class 9 RID class 9

ADR/RID packing group ---- Hazard Identification No.

Substance Identification No. 3077 UN number 3077

Environmentally hazard us substance, solid, n.o.s.

Proper Shipping Name (Diotolylguanidine)

Sea transport (IMDG-code/ IMO)

Correct technical name ----- IMDG Class

UN Number -----

Packaging group

EMS Number ----

Air transport (ICAO-TI/ IATA-DGR)

ICAO-TI/IATA-DGR Class 9 UN number 3077

Packing group Environmentally hazardous substance, solid, n.o.s.

Correct technical name (Diotolylguanidine)

15. REGULATORY INFORMATION



Room 501,2-3 Unit No.8,Zhengzhou Road,Qingdao,China. TEL: <u>86 18661665800</u> Email: <u>Dana@ylsch-rbb.com</u> Website: <u>www.ylsch-rbb.com</u>

Chemical description Diotolylguanidine

Labelling according to EC directives

EC-number See section 2

Annex-1 to directive 67/548/EEC

Classification based on R 43 May cause sensitization by skin contact

May cause long-term adverse effects in the aquatic

environment

R(isk) phrase(s) S 24 Avoid contact with skin

S 37 Wear suitable gloves

S 60 This material and its container must be disposed of

as hazardous waste

S(afety) phrase(s) S 61 Avoid release to the environment. Refer to special

instruction /Safety data sheets

Other information To be displayed on the label: "EC label".

Wassergefährdungsklasse (WGK) ------

16.OTHER INFORMATION

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.